

Paintworks Specification NZ 325.1

System Wattyl Colourwood All in One Stain

Substrate Interior – New timber

Category Combined Stain and Clear finish, Wattyl Colourwood All in One Stain – Turps based

Product Features

Wattyl Colourwood All in One Stain is a convenient combined stain and clear finish that protects and beautifies all interior timber surfaces.

Surface Preparation – Refer to section 4 of the Wattyl Specifiers Manual

Minimum Surface Preparation. Ensure all new timber is free of dirt or grease and dry. Fill nail holes or cracks with Wattyl Timber Putty in a matching colour. Allow to dry. Sand smooth and remove dust.

Application Details	Data Sheet	Coverage m ² /L	Film Thickness (microns)		Dry Times (minimum)	
			Wet	Dry	Touch	Recoat
First Coat: Wattyl Colourwood All in One Satin Stain <i>(equipment: brush)</i>	WA162	10-14	71 to 100	28-39	4 hours	24 hours
Second Coat Wattyl Colourwood All in One Satin Stain <i>(equipment: brush)</i>	WA162	10-14	71 to 100	28-39	4 hours	24 hours

Recommended Uses For interior use only.
Suitable for use on all interior woodwork, louvre doors, built-in furniture and panelling.

Additional Notes **Not** suitable for MDF board unless previously sealed with Wattyl Estapol Speed – Gloss/Satin (WA184).
Before application test the colour on a timber off cut or a section of the job which is not visible. If the colour is too strong, thin up to 10% with mineral turps. To deepen the colour, apply additional coats of Wattyl Colourwood All in One Stain. Where the desired colour is achieved in one coat, apply two coats of Wattyl Estapol Gloss/Satin/Matt (WA181-3), over the colour to achieve the required film build.

Caution Provide adequate ventilation during use.
Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheet (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the (MSDS) and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.
3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If this datasheet is greater than 3 years old at the time of reading, or if you require further information please contact your nearest Wattyl Office.
4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.