

Paintworks Specification NZ 345.1

System Watty Forestwood Combat overcoated with Watty Forestwood Traditional Oil Stain

Substrate Exterior – New timber

Category Exterior clear water repellent timber preparation over coated with a Traditional Oil Stain –turps based oil fortified semi clear stain.

Product Features

Watty Forestwood Combat is ideal as a pre treatment for use on external joinery, beams and weatherboards. It is especially recommended on L.O.S.P treated timbers intended for finishing with an oil stain, as it reduces the likelihood of surface mould disfiguring the finish.

Watty Forestwood Traditional Oil Stain is a durable see-through, oil-fortified stain which adds colour to bare timber, but allows the grain to show through. Watty Forestwood Traditional Oil Stain penetrates and enhances the timbers natural beauty whilst preserving and protecting the surface.

Surface Preparation – Refer to section 4 of the Watty Specifiers Manual

Minimum Surface Preparation. Ensure timber is clean, dry and free from dirt, grease, oil and other contaminants.

We advise smooth (dressed) surfaces be left to weather for two weeks to loose their polished surface and improve stain uptake. *An initial coat of Watty Forestwood Combat applied to all surfaces, face, laps, end grain, and if possible the reverse of weatherboards will significantly improve mould resistance and timber stability.

Exterior ply in particular benefits from this extra treatment.

Leave the Watty Forestwood Combat to dry for a minimum of two hours and a maximum of 7 days before applying Watty Forestwood Traditional Oil Stain.

Application Details	Data Sheet	Coverage m ² /L	Film Thickness (microns)		Dry Times (minimum)	
			Wet	Dry	Touch	Recoat
First Coat: Watty Forestwood Combat (equipment: brush & speedbrush)	WA154	4-8	N/A	N/A	2 hours	When dry within 7 days
First Coat: Watty Forestwood Traditional Oil Stain (equipment: brush & speedbrush)	WA150	4-12	N/A	N/A	6 hours	24 hours
Second Coat (optional) Watty Forestwood Traditional Oil (equipment: brush & speedbrush)	WA150	4-12	N/A	N/A	6 hours	24 hours

Recommended Uses For exterior use on bare timber only. Ideal for all rough sawn and smooth timber. Suitable for use on exterior timber weatherboards, window frames, verandas, pergolas and other exterior timber areas.

Additional Notes Watty Forestwood Combat should only be used over bare timber and overcoated with stain within seven days of application.
Not suitable for previously primed, painted, badly weathered or damaged timber.

Caution Provide adequate ventilation during use.
Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

- This information is provided with respect to the listed Watty products. Watty recommends that: (a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheet (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty; (c) the product be transported, stored and handled in accordance with the information on the Material Safety Data Sheet (MSDS) and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
- The information in this technical data sheet was prepared using information gathered during product development. While Watty endeavours to update this information and maintain the accuracy and currency of its contents, Watty cannot guarantee that the information provided is wholly comprehensive.
- Watty recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If this datasheet is greater than 3 years old at the time of reading, or if you require further information please contact your nearest Watty Office.
- To the full extent permitted by law, Watty's liability for breach of a condition or warranty implied into the contract for sale between Watty and you by law is limited at Watty's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.