

Paintworks Specification NZ 350.1

System Watty Forestwood Aquatech Oil Stain

Substrate Exterior – New timber

Category Exterior Water thinned Oil Stain –water based oil fortified semi clear stain.

Product Features

A see-through water thinned oil stain for exterior timber weatherboards, verandas and pergolas in new or good condition. Watty Forestwood Aquatech Oil Stain adds natural colour whilst penetrating the timber. Available in a range of exciting colours. Watty Forestwood Aquatech Oil Stain enhances the natural beauty of the timber, allowing the grain pattern to show through. It must be regarded as a maintainable coating with less life expectancy than opaque paint.

Surface Preparation – Refer to section 4 of the Watty Specifiers Manual

Minimum Surface Preparation. Ensure timber is clean, dry and free from dirt, grease, oil and other contaminants.

We advise smooth (dressed) surfaces be left to weather for two weeks to loose their polished surface and improve stain uptake

Application Details	Data Sheet	Coverage m ² /L	Film Thickness (microns)		Dry Times (minimum)	
			Wet	Dry	Touch	Recoat
First Coat: Watty Forestwood Aquatech Oil Stain <i>(equipment: brush, speedbrush)</i>	WA151	4-12	N/A	N/A	4 hours	24 hours
Second Coat (optional) Watty Forestwood Aquatech Oil Stain <i>(equipment: brush, speedbrush)</i>	WA151	4-12	N/A	N/A	4 hours	24 hours

Recommended Uses

For exterior use on bare timber only. Ideal for all rough sawn and smooth timber. Suitable for use on exterior timber weatherboards, window frames, verandas, pergolas and other exterior timber areas.

Additional Notes

4 M²/L for durable rough sawn soft wood, 12 M²/L for smooth hardwood. Watty Forestwood Aquatech Oil Stain should only be used over bare timber or previously weathered oil stained surfaces.
Not suitable for previously primed, painted, badly weather or damaged timber.

Caution

Provide adequate ventilation during use. Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

- This information is provided with respect to the listed Watty products. Watty recommends that: (a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheet (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty; (c) the product be transported, stored and handled in accordance with the information on the Material Safety Data Sheet (MSDS) and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
- The information in this technical data sheet was prepared using information gathered during product development. While Watty endeavours to update this information and maintain the accuracy and currency of its contents, Watty cannot guarantee that the information provided is wholly comprehensive.
- Watty recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If this datasheet is greater than 3 years old at the time of reading, or if you require further information please contact your nearest Watty Office.
- To the full extent permitted by law, Watty's liability for breach of a condition or warranty implied into the contract for sale between Watty and you by law is limited at Watty's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.