

# Paintworks Specification NZ 370.1

**System** Watty Estapol Slate and Pebble Clear

**Substrate** Interior / Exterior – clear finish for slate, pebble, concrete and clay pavers.

**Category** Interior / Exterior Solution Acrylic clear finish.

**Product Features**

Watty Estapol Slate and Pebble Clear provides a tough protective coating for a range of interior and exterior surfaces. It will help resist penetration from spillages such as oil, grease and food, and is suitable for application to surfaces subject to domestic foot traffic. It helps bind exposed aggregate and pebblecrete while strengthening masonry surfaces against eroding and dusting. Watty Estapol Slate and Pebble Clear will not yellow over time

**Surface Preparation – Refer to section 4 of the Watty Specifiers Manual**

Minimum Surface Preparation. Before application, ensure the surface is thoroughly dry and free from dirt, grease, wax, efflorescence (white salts), or any loose flaking material. If mould is present treat with mould killer diluted 4:1 in water, brush on, leave 30 minutes, rinse off and allow to dry otherwise wash the surface with warm water and household detergent. If necessary, ensure removal of any grease, oil, wax or polish with Mineral Turpentine

If the existing coating is unsound, remove the previous coating with Watty Stripaway or Watty Estapol Slate and Pebble Clear Reducer prior to recoating. New concrete surfaces should be left to fully cure for approximately 4 - 6 weeks.

All cracks or damaged areas should be repaired prior to application.

Smooth troweled concrete surfaces should be acid etched to ensure maximum adhesion of coating.

Allow new grouting to dry for at least 2 weeks prior to finishing.

Application Details	Data Sheet	Coverage m <sup>2</sup> /L	Film Thickness (microns)		Dry Times (minimum)	
			Wet	Dry	Touch	Recoat
First Coat: <b>Watty Estapol Slate and Pebble Clear</b> (equipment: brush or woollen roller)	WA171	10-14	N/A	17-24	1 hour	3 hours
Second Coat (optional) <b>Watty Estapol Slate and Pebble Clear</b> (equipment: brush or woollen roller)	WA171	10-14	N/A	17-24	1 hour	3 hours

**Recommended Uses**

Exposed aggregate, slate Pebble finishes Concrete (including stamped) Clay pavers, unglazed quarry tiles, Brick, Sandstone.

**Additional Notes**

Not suitable for use on glazed quarry tiles, rubber, vinyl, linoleum, areas exposed to salt water, timber surfaces or bitumen. Not recommended for areas exposed to direct flame or extreme heat (e.g. barbeque and fireplace surrounds). Not recommended for drive on surfaces e.g. garage floors or driveways.

**Caution**

Provide adequate ventilation during use.

Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

- This information is provided with respect to the listed Watty products. Watty recommends that: (a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheet (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty; (c) the product be transported, stored and handled in accordance with the information on the Material Safety Data Sheet (MSDS) and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
- The information in this technical data sheet was prepared using information gathered during product development. While Watty endeavours to update this information and maintain the accuracy and currency of its contents, Watty cannot guarantee that the information provided is wholly comprehensive.
- Watty recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If this datasheet is greater than 3 years old at the time of reading, or if you require further information please contact your nearest Watty Office.
- To the full extent permitted by law, Watty's liability for breach of a condition or warranty implied into the contract for sale between Watty and you by law is limited to Watty's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.