

# Paintworks Specification NZ125P/TU

System	Taubmans LivingProof
Substrate	New interior paper faced plasterboard
Area	Walls – General Areas
Gloss levels	Eggshell, Silk, Satin, Matt
Category	Premium water based acrylic
Description	Taubmans LivingProof is a 100% acrylic wall paint with superior feel and appearance, excellent covering power and adhesion. It applies with minimum roller spatter, superior scrubability together with excellent stain removal properties, scuff resistance, outstanding durability and washability

**Surface Preparation: Refer to Section 4 of the Watty Specifiers Manual**

Minimum surface preparation: Ensure the surface is clean and dry. Fill any holes or surface imperfections with a spackling compound. Sand the filled areas and wipe down to remove sanding dust. Do not sand the uncoated paper faced plasterboard.

Application recommendations	Data Sheet	Coverage m <sup>2</sup> /L	Film thickness (microns)		Dry times (minimum hrs)	
			Wet	Dry	Touch	Recoat
First coat applied by brush, roller or spray (must be back rolled)						
Taubmans Tradex Freesand Sealer Undercoat	TA088	8 - 14	70 - 125	35 – 50	1/2	2
Second coat applied by brush, roller or spray						
Taubmans LivingProof Eggshell / Silk / Satin / Matt	TA040 – TA043	14 - 16	60 – 75	25 – 35	1/2	2
Third coat applied by brush, roller or spray						
Taubmans LivingProof Eggshell / Silk / Satin / Matt	TA040 – TA043	14 - 16	60 - 75	25 – 35	1/2	2

Recommended uses:	Ideal for domestic passage ways and other high usage living areas. For interior use only
Additional notes:	Leave for seven days after application of final coat before cleaning (tinted colours require up to two weeks). Dry times are measured at 20°C and 65% humidity, lower temperatures and higher humidity will prolong these times by up to 100%
Caution	Provide adequate ventilation during use. Application should not be carried out if the air or substrate temperature is below 5°C or above 35°C, or the humidity is greater than 80%. The temperature must not fall below 5°C during the drying process.

1. This information is provided with respect to the listed Watty products. Watty recommends that:  
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheet (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty; (c) the product be transported, stored and handled in accordance with the information on the (MSDS) and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Watty endeavours to update this information and maintain the accuracy and currency of its contents, Watty cannot guarantee that the information provided is wholly comprehensive.

3. Watty recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If this datasheet is greater than 3 years old at the time of reading, or if you require further information please contact your nearest Watty Office.

4. To the full extent permitted by law, Watty's liability for breach of a condition or warranty implied into the contract for sale between Watty and you by law is limited at Watty's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.