

System	Taubmans EcoProof Ceiling Paint
Substrate	New interior paper faced plasterboard
Area	Ceilings – General Areas
Gloss levels	Flat
Category	Premium water based acrylic – Low VOC
Description	Taubmans EcoProof Ceiling Paint is a premium quality interior acrylic paint. It is an environmentally friendly coating with near zero Volatile Organic Compounds (VOC's) and nil paint odours. Taubmans EcoProof Ceiling paint produces a smooth flat white, long lasting elegant finish.

Surface Preparation: Refer to Section 4 of the Watty Specifiers Manual

Minimum surface preparation: Ensure the surface is clean and dry. Fill any holes or surface imperfections with appropriate filler. Sand the filled areas and wipe down to remove sanding dust. Do not sand the uncoated paper faced plasterboard.

Application recommendations	Data Sheet	Coverage m ² /L	Film thickness (microns)		Dry times (minimum hrs)	
			Wet	Dry	Touch	Recoat
First coat applied by brush, roller or spray (must be back rolled)						
Taubmans EcoProof Primer Undercoat	TA061	10 - 14	70 - 125	35 - 50	1/2	2
Second coat applied by brush, roller or spray:						
Taubmans EcoProof Ceiling Paint	TA060	14 - 16	60 - 70	25 - 30	1/2	2
Third coat applied by brush, roller or spray:						
Taubmans EcoProof Ceiling Paint	TA060	14 - 16	60 - 70	25 - 30	1/2	2

Recommended uses: Ideal for ceilings in bedrooms, living rooms, children's rooms; for health institutions e.g. hospitals, nursing homes, rest homes; schools.
For interior use only

Additional notes: Should cleaning be required, remove grime with a soft cloth, warm water and detergent, and then pat dry with a clean cloth. Do not use abrasive cleaners, or rub vigorously, as polishing may occur.
Dry times are measured at 20°C and 65% humidity, lower temperatures and higher humidity will prolong these times by up to 100%

Caution Provide adequate ventilation during use.
Application should not be carried out if the air or substrate temperature is below 5°C or above 35°C, or the humidity is greater than 80%. The temperature must not fall below 5°C during the drying process.
Not recommended for use in kitchens, bathrooms and laundries.

1. This information is provided with respect to the listed Watty products. Watty recommends that:
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheet (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty; (c) the product be transported, stored and handled in accordance with the information on the (MSDS) and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Watty endeavours to update this information and maintain the accuracy and currency of its contents, Watty cannot guarantee that the information provided is wholly comprehensive.

3. Watty recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If this datasheet is greater than 3 years old at the time of reading, or if you require further information please contact your nearest Watty Office.

4. To the full extent permitted by law, Watty's liability for breach of a condition or warranty implied into the contract for sale between Watty and you by law is limited at Watty's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.