

# Paintworks Specification NZ200T

System	Taubmans Tradex Ceiling Flat
Substrate	New interior paper faced plasterboard
Area	Ceilings – General Areas
Gloss levels	Flat
Category	Trade water based vinyl
Description	An interior, tintable vinyl finish with no side sheen especially for ceilings in living areas. It produces a matt decorative finish with no side sheen, dries quickly to a smooth even finish, ideal on critically lit ceilings together with low odour.

**Surface Preparation: Refer to Section 4 of the Watty! Specifiers Manual**

Minimum surface preparation: Ensure the surface is clean and dry. Fill any holes or surface imperfections with a proprietary filler. Sand the filled areas and wipe down to remove sanding dust. Do not sand the uncoated paper faced plasterboard.

Application recommendations	Data Sheet	Coverage m <sup>2</sup> /L	Film thickness (microns)		Dry times (minimum hrs)	
			Wet	Dry	Touch	Recoat
First coat applied by brush, roller or spray (must be back rolled):						
Taubmans Tradex Freesand Sealer Undercoat	TA088	8 - 14	70 - 125	35 - 50	1	2
Second coat applied by brush, roller or spray:						
Taubmans Tradex Ceiling Flat	TA080	14 - 16	35 - 45	17 - 19	1/2	2
Third coat applied by brush, roller or spray:						
Taubmans Tradex Ceiling Flat	TA080	14 - 16	35 - 45	17 - 19	1/2	2

**Recommended uses:** Ideal for ceilings in bedrooms, living rooms, dining rooms and living areas.  
For interior use only.

**Additional notes:** Should cleaning be required, remove grime with a soft cloth, warm water and detergent, and then pat dry with a clean cloth. Do not use abrasive cleaners, or rub vigorously, as polishing may occur.  
Dry times are measured at 20°C and 65% humidity, lower temperatures and higher humidity will prolong these times by up to 100%.

**Caution** Provide adequate ventilation during use, allow air circulation and ensure positive drying.  
Application should not be carried out if the air or substrate temperature is below 10°C or above 35°C, or the humidity is greater than 85%. The temperature must not fall below 10°C during the drying process.

1. This information is provided with respect to the listed Watty! products. Watty! recommends that:  
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheet (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty!; (c) the product be transported, stored and handled in accordance with the information on the (MSDS) and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Watty! endeavours to update this information and maintain the accuracy and currency of its contents, Watty! cannot guarantee that the information provided is wholly comprehensive.

3. Watty! recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If this datasheet is greater than 3 years old at the time of reading, or if you require further information please contact your nearest Watty! Office.

4. To the full extent permitted by law, Watty!'s liability for breach of a condition or warranty implied into the contract for sale between Watty! and you by law is limited at Watty!'s election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.