

Paintworks Specification NZ220P/TU

System	Taubmans UltraProof Acrylic Enamel Satin / Eggshell
Substrate	New interior paper faced plasterboard
Area	Ceilings - Wet Service Areas: Ventilated
Gloss levels	Satin, Eggshell
Category	Premium water based acrylic enamel
Description	Taubmans UltraProof Satin / Eggshell Acrylic Enamel is an advanced formulation acrylic with enamel-like characteristics for interior and exterior use. It combines the smooth finishing properties and serviceability of enamels with the low odor, quick dry and convenience of water based finishes. It produces rapid dry, non yellowing decorative finish.

Surface Preparation: Refer to Section 4 of the Watty Specifiers Manual

Minimum surface preparation: Ensure the surface is clean and dry. Fill any holes or surface imperfections with a suitable filler. Sand the filled areas, finish sand all surface to a very high standard, wipe down to remove sanding dust. Do not sand the uncoated paper faced plasterboard.

Application recommendations	Data Sheet	Coverage m ² /L	Film thickness (microns)		Dry times (minimum hrs)	
			Wet	Dry	Touch	Recoat
First coat applied by brush, roller or spray (must be back rolled):						
Taubmans Tradex Pigmented Sealer	TA073	8 - 14	70 - 125	35 - 61	2	6
Second coat applied by brush, roller or spray:						
Taubmans UltraProof Acrylic Enamel Satin / Eggshell	TA048, TA057	14 - 16	60 - 70	23 - 26	1/2	4
Third coat applied by brush, roller or spray:						
Taubmans UltraProof Acrylic Enamel Satin / Eggshell	TA048, TA057	14 - 16	60 - 70	23 - 26	1/2	4

Recommended uses: Ideal for ceilings in ventilated wet areas e.g. domestic bathrooms, laundries and kitchens. Eggshell is not recommended in areas with critical lighting.

Additional notes: Leave seven days after application of final coat before washing. When subject to steam or condensation, water based paints may develop a stain, which can be removed with a damp cloth. Avoid such exposure for the first 48 hours after application of the final coat. Dry times are measured at 20°C and 65% humidity, lower temperatures and higher humidity will prolong these times by up to 100%.

Caution Provide adequate ventilation during use. Application should not be carried out if the air or substrate temperature is below 10°C or above 35°C, or the humidity is greater than 85%. The temperature must not fall below 10°C during the drying process.

1. This information is provided with respect to the listed Watty products. Watty recommends that:
 (a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheet (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty; (c) the product be transported, stored and handled in accordance with the information on the (MSDS) and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Watty endeavours to update this information and maintain the accuracy and currency of its contents, Watty cannot guarantee that the information provided is wholly comprehensive.

3. Watty recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If this datasheet is greater than 3 years old at the time of reading, or if you require further information please contact your nearest Watty Office.

4. To the full extent permitted by law, Watty's liability for breach of a condition or warranty implied into the contract for sale between Watty and you by law is limited at Watty's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.