

# Paintworks Specification NZ214.1P

System	Taubmans Solpah Acrylic Paving Paint
Substrate	Previously painted interior & exterior oil based/enamel finishes
Area	Floors – General Areas Light Use
Gloss levels	Satin
Category	Premium water based acrylic
Description	Taubmans Solpah Acrylic Paving Paint is a tough, water based, acrylic finish for exterior and interior surfaces such a paths, floor and decks. Protects and beautifies walk on surfaces. Provides a safe walking surface on both flat and sloping surfaces when Taubmans Solpah Low Slip Additive is used.

**Surface Preparation. Refer to section 4 of the Watty Specifiers Manual**

Minimum surface preparation. Ensure the surface is clean and dry. All loose, peeling and flaking material must be removed with a scraper. Remove all gloss on painted surfaces with 220 abrasive paper. Fill holes and cracks with a suitable filling compound, block down, sand to an even finish, dust off. On bare areas treat as for new work.

Application recommendations	Data Sheet	Coverage m <sup>2</sup> /L	Film thickness (microns)		Dry times (minimum hrs)	
			Wet	Dry	Touch	Recoat
First coat applied by brush, roller or spray (must be back rolled)						
Taubmans Solpah Acrylic Paving Paint	TA032	8 - 16	83	35	1	4
Second coat applied by brush, roller or spray						
Taubmans Solpah Acrylic Paving Paint	TA032	8 - 16	83	35	1	4

Recommended uses: For use on suitably prepared interior concrete floors

Additional notes: For a low slip finish use Taubmans Low Slip Additive  
Not suitable for industrial floors or drive on surfaces  
Dry times are measured at 20°C and 65% humidity, lower temperatures and higher humidity will prolong these times by up to 100%

Caution Provide adequate ventilation during use.  
Application should not be carried out if the air or substrate temperature is below 5°C or above 35°C, or the humidity is greater than 80%. The temperature must not fall below 5°C during the drying process.

1. This information is provided with respect to the listed Watty products. Watty recommends that:  
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheet (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty; (c) the product be transported, stored and handled in accordance with the information on the (MSDS) and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Watty endeavours to update this information and maintain the accuracy and currency of its contents, Watty cannot guarantee that the information provided is wholly comprehensive.

3. Watty recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If this datasheet is greater than 3 years old at the time of reading, or if you require further information please contact your nearest Watty Office.

4. To the full extent permitted by law, Watty's liability for breach of a condition or warranty implied into the contract for sale between Watty and you by law is limited at Watty's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.