

System	Taubmans Aquafloor Waterbased Epoxy
Substrate	Previously painted interior & exterior oil based/enamel finishes
Area	Floors – General Areas Light Industrial Use
Gloss levels	Satin
Category	Premium water based epoxy – Low VOC
Description	Taubmans Aquafloor Water Based Epoxy is an environmentally friendly two pack epoxy coating for garage, warehouse and workshop concrete floors. It has a low odour and low volatile organic content (VOC). Taubmans Aquafloor Water Based Epoxy is hard wearing and resistant to petrol, engine oil and hydraulic oil. It may be applied by brush, roller or airless spray and all equipment is cleaned up with water.

Surface Preparation. Refer to section 4 of the Watty Specifiers Manual

Minimum surface preparation. Ensure the surface is clean and dry. All loose, peeling and flaking material must be removed with a scraper. Remove all gloss on painted surfaces with 220 abrasive paper. Fill holes and cracks with a suitable filling compound, block down, sand to an even finish, dust off. On bare areas treat as for new work.

Application recommendations	Data Sheet	Coverage m ² /L	Film thickness (microns)		Dry times (minimum hrs)	
			Wet	Dry	Touch	Recoat
First coat applied by roller or spray (must be back rolled)						
Taubmans Aquafloor Waterbased Epoxy	TA062	12 - 15	100	40	30 min	4
Second coat applied by roller or spray						
Taubmans Aquafloor Waterbased Epoxy	TA062	12 - 15	100	40	30 min	4

Recommended uses: For use on suitably prepared interior concrete floors

Additional notes: For a low slip finish use Taubmans Low Slip Additive
Dry times are measured at 20°C and 65% humidity, lower temperatures and higher humidity will prolong these times by up to 100%

Caution Do not apply when the temperature is below 8°C, the humidity is greater than 85% or if dew or rainfall is likely within 4 hours of application
Due to the nature and variety of compounds used in the manufacture of vehicle tyres no guarantee can be provided for adhesion of Aquafloor to concrete surfaces over which tyres have previously tracked or sat.
With new concrete no guarantee can be provided for adhesion to the area where the tyres of a vehicle rest.
This product is not intended for waterproofing porous concrete.
Do not apply to concrete where a silicate hardener has been applied.

1. This information is provided with respect to the listed Watty products. Watty recommends that:
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheet (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty; (c) the product be transported, stored and handled in accordance with the information on the (MSDS) and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Watty endeavours to update this information and maintain the accuracy and currency of its contents, Watty cannot guarantee that the information provided is wholly comprehensive.

3. Watty recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If this datasheet is greater than 3 years old at the time of reading, or if you require further information please contact your nearest Watty Office.

4. To the full extent permitted by law, Watty's liability for breach of a condition or warranty implied into the contract for sale between Watty and you by law is limited at Watty's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.