

Wattyl Roofgard Antimould Prewash

PRODUCT DESCRIPTION

A concentrated mould, moss and lichen killer with residual activity.

INTENDED USES – EXTERIOR

- Stone chip coated roofs
- Concrete/ clay tiles
- General surface cleaning

TECHNICAL DATA

- Vehicle Type QUAT
- Pigmentation None
- Solvent Water
- Pot Life Not applicable
- Finish Not applicable
- Colour Not applicable
- Touch Dry Time Not applicable
- Recoat Time Leave for 24-28 hours
- Preparatory Coat Not required
- Theoretical Coverage Apply to saturation, typically around 3-5m²/L when diluted
- Dry Film Thickness Not applicable
- Usual Number of Coats 1
- Toxicity of dry film Non Toxic
- Durability Not applicable
- Thinning and Clean Up Clean Water
- V.O.C. Not applicable
- Pack Sizes 20L

PERFORMANCE PARAMETERS

Features

- It kills existing growth, loosens it from the surface and prevents re-contamination before coating.
- May be used as a mould killer as part of normal maintenance

Constraints

- Do not apply on wet surfaces.
- Roofs that collect drinking water must have down pipes disconnected before treatment commences and not re-connected until 50mm or more of rain has fallen after completion.

SURFACE PREPARATION

Remove gross contamination before treatment by brushing or brooming

APPLICATION

Heavy Mould:

Mix one part concentrate with one part clean water.

Light Mould:

Mix one part concentrate with three parts clean water.

Apply to saturation using a bucket and broom, knapsack sprayer or watering can. Leave for 24-48 hours.

Power wash (750 - 1200psi) the surface to remove dead material, dirt and other contaminants.

Care must be taken not to damage friable concrete/clay tiles.

NOTES



When used as part of a maintenance program, improved residual activity will be achieved if, after the initial treatment, a second application is carried out and allowed to dry without rinsing.

MATERIAL SAFETY DATA SHEETS

Wattyl (N.Z) Ltd Material Safety Data Sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products, and are available on request.

NOTE: The information concerning the use and application of these products is intended for use by professional specifiers and is believed to be correct at the date of printing, and is given in good faith. Wattyl (NZ) Ltd reserves the right to alter the product or specification without notice. The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.

Wattyl (N.Z.) Limited, P. O. Box 1545, Auckland, 1. Phone 09 820 6700 Fax 09 820 6572



WATTYL (NZ) LTD

INFORMATION HELP LINE: 0800 735551 (New Zealand)