

# Wattyl Roadmarking

## PRODUCT DESCRIPTION

A tough, quick drying water resistant chlorinated rubber finish formulated with bright pigments for high visibility. Wattyl Roadmarking is intended for application to concrete, bitumen and other road and paving surfaces providing marking for parking bays, lanes etc.

Wattyl Roadmarking is formulated to be easier to use than professional road marking paints making it possible for individuals and organizations to undertake small scale marking operations.

## INTENDED USES – EXTERIOR

- Lane marking road surfaces, paving and concrete floors.

## TECHNICAL DATA

- |                         |  |
|-------------------------|--|
| • Vehicle Type          | Chlorinated rubber blend   |
| • Pigmentation          | Inorganic oxides, and chromates  |
| • Solvent               | Aromatic hydrocarbon   |
| • Pot Life              | Not applicable   |
| • Finish                | Flat (gloss at 60° <3%)  |
| • Colour                | White and Yellow   |
| • Touch Dry Time        | 30 minutes at 20°C & 65% RH  |
| • Recoat Time           | Not normally required  |
| • Preparatory Coat      | Not required   |
| • Theoretical Coverage  | Up to 10m <sup>2</sup> /L. Coverage will be lower on rough or absorbent surfaces |
| • Dry Film Thickness    | 50µ at 10m <sup>2</sup> /L   |
| • Usual Number of Coats | 1  |
| • Toxicity of dry film  | Yellow contains lead chromate pigments   |
| • Durability            | Good   |
| • Thinning and Clean Up | Wattyl Spraying Thinners   |
| • V.O.C.                | >300 g/L as per EC-07-07   |
| • Pack Sizes            | 1L, 4L, 10L  |

## PERFORMANCE PARAMETERS

### Features

- Gives bright markings which are self cleaning.

### Constraints

- Do not apply indoors as self cleaning will not occur, indoors use a quick drying enamel
- On synthetic surfaces (Astroturf, Tartan™ track, etc) we recommend testing compatibility before use.

## SURFACE PREPARATION

Ensure surface is in sound condition. Remove grease, oil etc.  
Fill cracks etc if required with an exterior grade filler.  
Surfaces to be painted must be dry before application of this product.

## APPLICATION

Stir thoroughly before and regularly during use. Apply by brush, roller or spray.

## NOTES



Wattyl Roadmarking Yellow contains Lead Chromate pigment. If spraying, always wear a mask that prevents inhalation of overspray.

## MATERIAL SAFETY DATA SHEETS

Wattyl (N.Z) Ltd Material Safety Data Sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products, and are available on request.

NOTE: The information concerning the use and application of these products is intended for use by professional specifiers and is believed to be correct at the date of printing, and is given in good faith. Wattyl (NZ) Ltd reserves the right to alter the product or specification without notice. The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.

Wattyl (N.Z.) Limited, P. O. Box 1545, Auckland, 1. Phone 09 820 6700 Fax 09 820 6572



WATTYL (NZ) LTD

INFORMATION HELP LINE: 0800 735551 (New Zealand)