

Wattyl Forestwood Combat

PRODUCT DESCRIPTION

Wattyl Forestwood Combat is a clear solvent based water repellent timber preparation designed primarily as a pre-treatment of timber surfaces to prevent warping, cracking and improve the performance of subsequently applied oil based stains.

INTENDED USES – EXTERIOR

- Ideal for use on exterior joinery, beams and weatherboards
- Recommended on LOSP treated timbers intended for finishing with an oil based stain, as it reduces the likelihood surface mould disfiguring the finish.

TECHNICAL DATA

- Vehicle Type Modified Oil
- Pigmentation Not applicable
- Solvent Mineral Turpentine
- Pot Life Not applicable
- Finish Matt oiled look
- Colour Clear
- Touch Dry Time 2 hours
- Recoat Time Stain within 7 days of application (see notes)
- Preparatory Coat Not required
- Theoretical Coverage 4 - 8 m²/L depending on porosity and texture of the surface
- Dry Film Thickness Not applicable
- Usual Number of Coats 1
- Toxicity of dry film Non Toxic
- Durability Good
- Thinning and Clean Up Mineral turpentine
- V.O.C. >300g/L as per EC-07-07
- Pack Sizes 4L,10L

PERFORMANCE PARAMETERS

Features

- Water repellence improves performance of subsequently applied stains.
- Protects timber from mould and fungus.

Constraints

- It is not intended as a timber finish in its own right and should be over coated within 7 days.
- Will retain water repellent properties for up to 12 weeks if not stained.
- Should not be applied to timbers that are to be painted, or varnished unless the treated timbers are wiped over with Mineral Turpentine to permit the first coats of varnish to key correctly.

SURFACE PREPARATION

Ensure timber is correctly treated and graded for exterior use.
Clean all surfaces of dirt, grease, mould etc with liquid sugar soap applied using a soft nylon brush.
Hose off and allow to dry.
Sanding should be carried out on smooth timbers only if absolutely required.
Water blasting should only be carried out by skilled applicators to avoid timber damage.

APPLICATION

Stir Wattyl Forestwood Combat thoroughly before and occasionally during use.
Pretreatment: Dip for 30 seconds or apply by brush very liberally to all faces. Pay careful attention to cut ends and lap joints.

NOTES



Wattyl Forestwood Combat should be over coated within 7 days.
Do not apply over paint or onto surfaces other than timber.

MATERIAL SAFETY DATA SHEETS

Wattyl (N.Z) Ltd Material Safety Data Sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products, and are available on request.

NOTE: The information concerning the use and application of these products is intended for use by professional specifiers and is believed to be correct at the date of printing, and is given in good faith. Wattyl (NZ) Ltd reserves the right to alter the product or specification without notice. The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.

Wattyl (N.Z.) Limited, P. O. Box 1545, Auckland, 1. Phone 09 820 6700 Fax 09 820 6572



WATTYL (NZ) LTD

INFORMATION HELP LINE: 0800 735551 (New Zealand)