

# Wattyl Forestwood Linseed Oil Fence Stain

## PRODUCT DESCRIPTION

A semi transparent natural oil stain designed to enrich the colour and grain of both rough sawn and dressed fencing timbers.

## INTENDED USES – EXTERIOR

- New and previously stained timber fences and retaining walls

## TECHNICAL DATA

- Vehicle Type Linseed Oil
- Pigmentation Oxide pigments
- Solvent Mineral Turpentine
- Pot Life Not applicable
- Finish Matt oiled look
- Colour Standard colours
- Touch Dry Time 24 hours at 20°C & 65% RH
- Recoat Time 48 hours at 20°C & 65% RH
- Preparatory Coat Not required
- Theoretical Coverage 4 -12m<sup>2</sup>/L depending on porosity and texture of the surface
- Dry Film Thickness Not applicable
- Usual Number of Coats 1 - 2
- Toxicity of dry film Non Toxic
- Durability Good
- Thinning and Clean Up Mineral Turpentine
- V.O.C. >300g/L as per EC-07-07
- Pack Sizes 5L

## PERFORMANCE PARAMETERS

### Features

- Adds colour to timber fences without concealing the grain.

### Constraints

- Not suitable for walk on surfaces or weatherboards.

## SURFACE PREPARATION

Ensure timber surface is in sound condition.

Remove any grease, dust, dirt, mildew, wax etc. On dressed face timbers an initial period of 2-3 weeks weathering before staining will improve penetration.

**Mould:** If mould is present remove as much mould growth as possible by scraping and stiff brushing. Apply a mixture of 1L hypochlorite bleach and 200mL liquid sugar soap in 3L of water by spray or brush. Leave for 30 minutes then hose off and allow the surface to dry. Alternatively a proprietary fungicidal wash may be used as directed.

## APPLICATION

Stir thoroughly with a flat stirrer before and occasionally during use.

Apply with a brush or speed brush to saturation of the timber.

## NOTES

### Caution:



Rags used with this product may constitute a fire hazard and should be soaked in water overnight before disposal.

## MATERIAL SAFETY DATA SHEETS

Wattyl (N.Z.) Ltd Material Safety Data Sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products, and are available on request.

NOTE: The information concerning the use and application of these products is intended for use by professional specifiers and is believed to be correct at the date of printing, and is given in good faith. Wattyl (NZ) Ltd reserves the right to alter the product or specification without notice. The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.

Wattyl (N.Z.) Limited, P. O. Box 1545, Auckland, 1. Phone 09 820 6700 Fax 09 820 6572



WATTYL (NZ) LTD

INFORMATION HELP LINE: 0800 735551 (New Zealand)