

# Wattyl Deck and Furniture Oil

## PRODUCT DESCRIPTION

Wattyl Deck and Furniture Oil helps protect and enhance the natural beauty of timber decks and garden furniture. It will highlight the natural grain, colour and texture of the timber.

## INTENDED USES – EXTERIOR

- Ideal for use on most decking and garden furniture timbers
- Ideal for rough sawn and smooth timber or over similar oil stains

## TECHNICAL DATA

- |                         |   |
|-------------------------|---|
| • Vehicle Type          | Modified Oil  |
| • Pigmentation          | Oxide Pigments  |
| • Solvent               | Mineral Turpentine  |
| • Pot Life              | Not applicable  |
| • Finish                | Matt oiled look   |
| • Colour                | Available in Natural Pine, Natural Teak, Natural Kwila                  |
| • Touch Dry Time        | Overnight   |
| • Recoat Time           | 24 hours (minimum)  |
| • Preparatory Coat      | Not required  |
| • Theoretical Coverage  | 4-12 m <sup>2</sup> /L depending on porosity and texture of the surface |
| • Dry Film Thickness    | Not applicable  |
| • Usual Number of Coats | 2   |
| • Toxicity of dry film  | Non Toxic   |
| • Durability            | Good  |
| • Thinning and Clean Up | Mineral turpentine  |
| • V.O.C.                | >300g/L as per EC-07-01   |
| • Pack Sizes            | 1L, 5L,10L  |

## PERFORMANCE PARAMETERS

### Features

- It adds colour to the timber but allows the grain to show through.
- Protects timber from mould and fungus.

### Constraints

- Wattyl Deck and Furniture Oil will assist in retaining the natural colour of the timber, but this will naturally fade and grey. When this occurs, further coats of Wattyl Deck and Furniture Oil may be applied.
- Not suitable for used over surfaces previously primed or coated with paint type finishes.

## SURFACE PREPARATION

**New Timber:** Allow new timber to weather for 2 months before oiling. Ensure the timber is dry and free from dirt, wax, grease or oil. Thoroughly clean the surface, use a mixture of household detergent and warm water, and then rinse off with clean water. The surface must be completely dry before applying Wattyl Deck and Furniture Oil.

**Previously Oiled:** Timber: Remove as much mould growth as possible by scraping or stiff brushing. Apply a mixture of 1L hypochlorite bleach and 20mL liquid sugar soap in 3 litres of water by spray or brush. Leave for 30 minutes then hose off and allow the surface to dry. Alternatively a proprietary fungicidal wash may be used as directed. Allow to dry thoroughly before reapplying Wattyl Deck and Furniture Oil.

## APPLICATION

Stir thoroughly before use and regularly during use with a broad, flat stirrer to ensure a uniform colour. For added colour consistency mix and box together all cans on site before use. Partly used cans of Wattyl Deck and Furniture Oil should be used within 3 months.

**Oiling:** Apply two coats of undiluted Wattyl Deck and Furniture Oil by brush or speed brush, working well into the timber. Allow to dry 24 hours between coats. Resist the temptation to apply excess oil, to be effective oils must penetrate the timber, not remain on the surface.

## NOTES

Wattyl Deck and Furniture Oil should only be used on bare timber or over previous oil stained surfaces. Do not apply over paint or onto surfaces other than timber.

**Maintenance:** We recommend regular (at least annual) washing of the surface to remove surface contaminants with a mixture of 250mls mould killer, 20mls liquid sugar soap and 3 litres of water applied with a soft brush. Hose off and allow the surface to dry.



Wattyl Deck and Furniture Oil must be regarded as a maintainable coating and should be re-applied every summer or as soon as the timber shows signs of weathering due to exposure.

## MATERIAL SAFETY DATA SHEETS

Wattyl (N.Z.) Ltd Material Safety Data Sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products, and are available on request.

NOTE: The information concerning the use and application of these products is intended for use by professional specifiers and is believed to be correct at the date of printing, and is given in good faith. Wattyl (NZ) Ltd reserves the right to alter the product or specification without notice. The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.

Wattyl (N.Z.) Limited, P. O. Box 1545, Auckland, 1. Phone 09 820 6700 Fax 09 820 6572



WATTYL (NZ) LTD

INFORMATION HELP LINE: 0800 735551 (New Zealand)