

Wattyl Forestwood Combat Water Based

PRODUCT DESCRIPTION

Wattyl Forestwood Combat Water Based is a timber treatment for exterior timber to prevent the growth of black mould which can cause unsightly staining of timber. Wattyl Forestwood Combat Water Based can be over coated with Wattyl exterior stains or left to weather if a cleaner, brighter silver grey appearance is desired.

INTENDED USES – EXTERIOR

For use on bare timber or over previously oil stained surfaces that have been weathered at least a year:

- Weatherboards
- Outdoor wooden furniture
- Wooden decks

TECHNICAL DATA

- | | |
|-------------------------|---|
| • Vehicle Type | Not applicable |
| • Pigmentation | Not applicable |
| • Solvent | Water |
| • Pot Life | Not applicable |
| • Finish | Not applicable |
| • Colour | Clear when dry, milky white in container |
| • Touch Dry Time | 1 hour at 20°C and 65%RH |
| • Recoat Time | May be stained after 24 hours at 20°C and 65%RH |
| • Preparatory Coat | Not applicable |
| • Theoretical Coverage | 4 – 12m ² /L depending on porosity of the timber |
| • Dry Film Thickness | Not applicable |
| • Usual Number of Coats | One |
| • Toxicity | Toxic to marine life |
| • Durability | Maintainable timber treatment |
| • Thinning and Clean Up | Water, away from drains |
| • V.O.C. | Not applicable |
| • Pack Size | 5L |

PERFORMANCE PARAMETERS

Features

- Prevents the growth of black mould for up to 24 months
- Can be used under Wattyl Forestwood Traditional Oil Stain, Wattyl Forestwood Aquatech, Wattyl Forestwood Decking Stain and Wattyl Deck and Furniture Oil
- May be used to inhibit mould growth on timber that is to be left to weather, giving a cleaner, brighter silver grey appearance over time

Constraints

- Do not use on dirty timber. This product will not kill existing mould and algae, it prevents their growth on clean timber.
- Do not use on wet timber as the Wattyl Forestwood Combat Water Based will not be absorbed into the timber
- Do not use on dense timber surfaces where the Wattyl Forestwood Combat Water Based may be washed off by rain.
- Does not contain UV inhibitors

SURFACE PREPARATION

Do not apply over paint or onto surfaces other than timber. Ensure timber is clean, dry and free from dirt, grease, oil and other contaminants. If mould is present remove as much mould growth as possible by scraping and stiff brushing. Apply a mixture of 1L hypochlorite bleach and 20mL liquid sugar soap in 3L of water by spray or brush. Leave for 30 minutes then hose off and allow the surface to dry. Alternatively a proprietary fungicidal wash may be used as directed.

APPLICATION

The timber must be absolutely dry prior to application. Shake the Forestwood Water Based Combat to ensure it is evenly mixed. Apply an even coat by brush. In interest of safety, application by spray is not recommended. Do not apply if dew or rainfall is likely within 4 hours of application.

Allow to dry before applying a stain over the Wattyl Forestwood Combat Water Based.

We recommend regular (at least annual) washing of the surface to remove surface contaminants with a mixture of 250mL hypochlorite bleach, 20mL liquid sugar soap, and 4L water applied with a soft brush. Hose off and allow to dry. Wattyl Forestwood Combat Water Based is a maintainable wood treatment and must be re-applied as soon as the timber starts showing signs of mould growth.

NOTES

Wattyl Forestwood Combat Water Based is toxic to fish. Do not let the product enter fishponds or streams. Do not dispose of clean up water or unused material into storm water drains. Do not use empty containers for storing food or drink.

MATERIAL SAFETY DATA SHEETS

Wattyl (N.Z.) Ltd Material Safety Data Sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products, and are available on request.

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:



(a) The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. (b) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (c) the product be used only in accordance with the information provided by Wattyl; (d) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (e) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.

Wattyl (N.Z.) Limited, P. O. Box 1545, Auckland, 1. Phone 09 820 6700 Fax 09 820 6572



WATTYL (NZ) LTD

INFORMATION HELP LINE: 0800 735551 (New Zealand)