

Wattyl Colourwood Timber Putty

PRODUCT DESCRIPTION

Wattyl Colourwood Timber Putty is a water based putty, suitable for filling nail holes, small cracks and imperfections in timber furniture, plywood paneling and other woodwork prior to finishing.

INTENDED USES – INTERIOR/EXTERIOR

- Furniture
- Plywood paneling
- Wood finishes

TECHNICAL DATA

- | | |
|-------------------------|--------------------------------------|
| • Vehicle Type | Acrylic |
| • Pigmentation | Fillers plus pigments |
| • Solvent | Water |
| • Pot Life | Not applicable |
| • Finish | Flat |
| • Colour | Available in a range of timber tones |
| • Touch Dry Time | 30 minutes at 20°C and 65% RH |
| • Recoat Time | 30 minutes at 20°C and 65% RH |
| • Preparatory Coat | Not required |
| • Theoretical Coverage | Not applicable |
| • Dry Film Thickness | Not applicable |
| • Usual Number of Coats | Not applicable |
| • Toxicity | Non toxic |
| • Durability | Must be over coated |
| • Thinning and Clean Up | Water |
| • V.O.C. | <5g/L as per EC-07-01 |
| • Pack Sizes | 95grams |



PERFORMANCE PARAMETERS

Features

- Suitable for interior use only.
- Quick drying and may be sanded after 30 minutes.
- Suitable under clear finishes including lacquer and French polish as well as paint.

Constraints

- Not for exterior use.
- Fill holes over 4mm deep or wide in several applications to prevent cracking due to shrinkage.

SURFACE PREPARATION

Ensure surface is clean, sound and dry. Sand smooth and remove all dust.

APPLICATION

Press putty lightly into position, leaving a little standing slightly proud of the surface. For deeper holes a second application should be made after the first coat has hardened sufficiently. Allow approximately 30 minutes, then sand smooth with 180-240 grade free-cut paper. Remove all traces of sanding dust prior to application of other coatings.

NOTES



Containers must be secured and stored upright during transit.
Containers must not be exposed to excessive heat and cold.

MATERIAL SAFETY DATA SHEETS

Wattyl (N.Z) Ltd Material Safety Data Sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products, and are available on request.

NOTE: The information concerning the use and application of these products is intended for use by professional specifiers and is believed to be correct at the date of printing, and is given in good faith. Wattyl (NZ) Ltd reserves the right to alter the product or specification without notice. The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.

Wattyl (N.Z.) Limited, P. O. Box 1545, Auckland, 1. Phone 09 820 6700 Fax 09 820 6572



WATTYL (NZ) LTD

INFORMATION HELP LINE: 0800 735551 (New Zealand)